

Pro1 - L47-696 : L47-696

Specifications ENERGY STAR Unique ID: 2383694 ENERGY STAR Partner: Pro1 IAQ, Inc Service Brand Name: Pro1 Service Model Name: L47-696 Service Model Number: L47-696 Thermostat Brand Owner: Pro1 IAQ, Inc. Thermostat Brand Name: PRO1 Thermostat Model Name: L47-696 Thermostat Model Name: L47-696 Thermostat Model Number: L47-696 Standby Power (W): 0.47 Thermostat Heating and Cooling Control Features: Temperature Detection, Time of Day Usage, Additional Home Temperatures Sensor, Humidity Sensing Thermostat Communication Method: Wi-Fi Demand Response Summary: The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: 2020-08-01 Date Certified: United States, Canada		
ENERGY STAR Partner: Pro1 IAQ, Inc Service Brand Name: Pro1 Service Model Name: L47-696 Service Model Number: L47-696 Thermostat Brand Owner: Pro1 IAQ, Inc. Thermostat Brand Name: PRO1 Thermostat Model Name: L47-696 Thermostat Model Number: L47-696 Thermostat Model Number: L47-696 Standby Power (W): 0.47 Thermostat Heating and Cooling Control Features: Temperature Detection, Time of Day Usage, Additional Home Temperature Sensor, Humidity Sensing Thermostat Communication Method: Wi-Fi The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters include arcepting an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: 2020-08-01 Date Certified: 2021-08-24 Markets: United States, Canada	Specifications	
Service Brand Name: Service Model Name: L47-696 Service Model Number: L47-696 Thermostat Brand Owner: Pro1 IAQ, Inc. Thermostat Brand Name: PRO1 Thermostat Model Name: L47-696 Thermostat Model Number: L47-696 Thermostat Model Number: L47-696 Standby Power (W): O.47 Thermostat Heating and Cooling Control Features: Thermostat Communication Method: Wi-Fi The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters in splal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: Date Certified: United States, Canada	ENERGY STAR Unique ID:	2383694
Service Model Name: L47-696 Service Model Number: L47-696 Thermostat Brand Owner: Pro1 IAQ, Inc. Thermostat Brand Name: PR01 Thermostat Model Number: L47-696 Thermostat Model Number: L47-696 Standby Power (W): Chermostat Heating and Cooling Control Features: Thermostat Heating and Cooling Control Features: Thermostat Communication Method: Demand Response Summary: The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: Date Certified: United States, Canada	ENERGY STAR Partner:	Pro1 IAQ, Inc
Service Model Number: Thermostat Brand Owner: Pro1 IAQ, Inc. Thermostat Brand Name: PRO1 Thermostat Model Name: L47-696 Thermostat Model Number: L47-696 Standby Power (W): 0.47 Thermostat Heating and Cooling Control Features: Temperature Detection, Time of Day Usage, Additional Home Temperatures: Thermostat Communication Method: Wi-Fi Demand Response Summary: The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: 2020-08-01 Date Certified: United States, Canada	Service Brand Name:	Pro1
Thermostat Brand Owner: Thermostat Brand Name: PRO1 Thermostat Model Name: L47-696 Standby Power (W): O.47 Thermostat Heating and Cooling Control Features: Thermostat Communication Method: Wi-Fi Demand Response Summary: The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: 2020-08-01 Date Certified: United States, Canada	Service Model Name:	L47-696
Thermostat Brand Name: Thermostat Model Name: L47-696 Thermostat Model Number: L47-696 Standby Power (W): Thermostat Heating and Cooling Control Features: Thermostat Communication Method: Demand Response Summary: The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: Date Certified: United States, Canada	Service Model Number:	L47-696
Thermostat Model Name: L47-696 Standby Power (W): Thermostat Heating and Cooling Control Features: Thermostat Communication Method: Demand Response Summary: The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: 2020-08-01 Date Certified: United States, Canada	Thermostat Brand Owner:	Pro1 IAQ, Inc.
Thermostat Model Number: Standby Power (W): O.47 Thermostat Heating and Cooling Control Features: Thermostat Communication Method: Demand Response Summary: The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: Date Certified: United States, Canada	Thermostat Brand Name:	PRO1
Standby Power (W): Thermostat Heating and Cooling Control Features: Thermostat Communication Method: Demand Response Summary: The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: 2020-08-01 Date Certified: United States, Canada	Thermostat Model Name:	L47-696
Thermostat Heating and Cooling Control Features: Thermostat Communication Method: Demand Response Summary: The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: Date Certified: United States, Canada	Thermostat Model Number:	L47-696
Thermostat Communication Method: Demand Response Summary: The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: 2020-08-01 Date Certified: United States, Canada	Standby Power (W):	0.47
Demand Response Summary: The Pro1 implementation of OpenADR 2.0b allows enrolled customers to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: 2020-08-01 Date Certified: United States, Canada		
to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully comply with capabilities listed in CEC Title 24, Part 6. Date Available on Market: 2020-08-01 Date Certified: 2021-08-24 Markets: United States, Canada	Thermostat Communication Method:	Wi-Fi
Date Certified: 2021-08-24 Markets: United States, Canada	Demand Response Summary:	to participate in load shedding events. Events can target specific devices via a variety of parameters including enrollment status and zip code. Upon receiving an event signal, the connected thermostat provides customers options on how it should respond. Options include accepting/denying the load shedding event. Work is in progress to fully
Markets: United States, Canada	Date Available on Market:	2020-08-01
	Date Certified:	2021-08-24
	Markets:	United States, Canada
ENERGY STAR Certified: Yes	ENERGY STAR Certified:	Yes

Captured On: 05/23/2025