## Zerova - ELECTRIC VEHICLE SUPPLY EQUIPMENT : AXLU111001D

| Brand Name: Zerova  Model Name: ELECTRIC VEHICLE SUPPLY EQUIPMENT  Model Number: AXLU111001D  ENERGY STAR Unique ID: 2440463  ENERGY STAR Partner: Zerova Technologies Taiwan Limited  Product Type: Level 2  Input Voltage (V): 240.0  Max Nameplate Output Current (A): 48  Maximum Output Power (kW): 11.52  Number of Outputs: 1  Maximum Output Cord Length (ft.): 18  Output Cord Gauge (AWG): 7  Maximum (100%) Measured Luminance of the High Res Display (candelas per m2): Automatic Brightness Control (ABC) Capable?: No |  |
|--|--|
| Model Name:  Model Number:  AXLU111001D  ENERGY STAR Unique ID:  ENERGY STAR Partner:  Zerova Technologies Taiwan Limited  Product Type:  Level 2  Input Voltage (V):  Max Nameplate Output Current (A):  Maximum Output Power (kW):  Number of Outputs:  Maximum Output Cord Length (ft.):  Maximum Output Cord Gauge (AWG):  Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?:  NO  |  |
| Model Number:  ENERGY STAR Unique ID:  2440463  ENERGY STAR Partner:  Zerova Technologies Taiwan Limited  Product Type:  Level 2  Input Voltage (V):  240.0  Max Nameplate Output Current (A):  Maximum Output Power (kW):  11.52  Number of Outputs:  1  Maximum Output Cord Length (ft.):  Maximum Output Cord Gauge (AWG):  7  Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?:  No   |  |
| ENERGY STAR Unique ID:  ENERGY STAR Partner:  Zerova Technologies Taiwan Limited  Product Type:  Level 2  Input Voltage (V):  Max Nameplate Output Current (A):  Maximum Output Power (kW):  Number of Outputs:  Maximum Output Cord Length (ft.):  Maximum Output Cord Gauge (AWG):  7  Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?:  No  |  |
| ENERGY STAR Partner:  Product Type: Level 2 Input Voltage (V):  Max Nameplate Output Current (A): Maximum Output Power (kW): Number of Outputs:  Maximum Output Cord Length (ft.):  Maximum Output Cord Gauge (AWG):  Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?:  No   |  |
| Product Type: Input Voltage (V):  Max Nameplate Output Current (A):  Maximum Output Power (kW):  Number of Outputs:  Maximum Output Cord Length (ft.):  Maximum Output Cord Gauge (AWG):  Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?:  No   |  |
| Input Voltage (V):  Max Nameplate Output Current (A):  Maximum Output Power (kW):  Number of Outputs:  Maximum Output Cord Length (ft.):  Output Cord Gauge (AWG):  Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?:  No   |  |
| Max Nameplate Output Current (A):  Maximum Output Power (kW):  Number of Outputs:  1  Maximum Output Cord Length (ft.):  Output Cord Gauge (AWG):  Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?:  No  |  |
| Maximum Output Power (kW):  Number of Outputs:  Maximum Output Cord Length (ft.):  Output Cord Gauge (AWG):  Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?:  No  |  |
| Number of Outputs:  Maximum Output Cord Length (ft.):  Output Cord Gauge (AWG):  Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?:  No  |  |
| Maximum Output Cord Length (ft.): 18  Output Cord Gauge (AWG): 7  Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?: No  |  |
| Output Cord Gauge (AWG):  Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?: No  |  |
| Maximum (100%) Measured Luminance of the High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?: No  |  |
| High Res Display (candelas per m2):  Automatic Brightness Control (ABC) Capable?: No   |  |
|  |  |
|  |  |
| Connected Capable: No  |  |
| Network Connection Types Available: Wi-Fi or Gigabit Ethernet, Cellular  |  |
| Is Broadband Internet Connection Needed for Demand Response?:  |  |
| Screen Area, if EVSE has high res display (in2): 10.77   |  |
| 15 A Operation Mode Test: Total Loss (watts): 2.0  |  |
| 30 A Operation Mode Test: Total Loss (watts): 4.0  |  |
| 4 A Operation Mode Test: Total Loss (watts): 1.0   |  |
| Full Current Operation Mode Test: Total Loss 10.0 (watts):   |  |
| Idle Mode Input Power (watts): 6.53  |  |
| Idle Mode Power Factor: 0.36   |  |
| Idle Mode Total Allowance (watts): 24.89   |  |
| No Vehicle Mode Input Power (watts): 4.27  |  |
| No Vehicle Mode Power Factor: 0.33   |  |
| No Vehicle Mode Total Allowance (watts): 4.81  |  |
| Partial On Mode Input Power (watts): 4.27  |  |
| Partial On Mode Power Factor: 0.33   |  |

| Partial On Mode Total Allowance (watts): | 4.81                  |
|--|-----------------------|
| Date Certified:                          | 2023-03-17            |
| Date Available on Market:                | 2023-03-17            |
| Markets:                                 | United States, Canada |
| ENERGY STAR Certified:                   | Yes                   |

## Additional Model Information

,AXLU111001W,

**Captured On:** 05/21/2025