

## XCHARGE - C6AM150CC : C6AM150CC

Specifications	
Brand Name:	XCHARGE
Model Name:	C6AM150CC
Model Number:	C6AM150CC
ENERGY STAR Unique ID:	2635745
Туре:	DC-output (AC-input)
Rated Input Voltage (V) AC-Input:	480
DC-input or AC-input:	AC-input
ENERGY STAR Partner:	XCharge Energy USA Inc
Maximum Nameplate Output Current (A) AC- Input:	200.0
Maximum Measured Luminance of the High Res Display (candelas per m2):	574.6
Output Cord Length (ft.):	16
Number of Outputs:	2
Output Cord Gauge (AWG):	2/0
Single Phase or Three Phase:	Three Phase
Product Configuration:	All-in-One Product Configuration
Maximum Available Output Power:	150000.0
Maximum Output Power:	150.0
Automatic Brightness Control Capable?:	No
Connected Capable:	Yes
Connects Using:	Wired Ethernet
Network Connection Types Available:	Gigabit Ethernet,Cellular
Screen Area, if EVSE has high res display (in2):	107.53
Connector Type:	Combined Charging System (CCS)
DR Protocol:	Open Charge Point Protocol (OCPP)
Is Broadband Internet Connection Needed for Demand Response?:	No
Network Security Standards:	None
Protocols Used to Support Smart Charging:	SAE J1772,ISO 15118-2 or later
Integral Battery Bank:	No
Product Features:	None
Auxiliary Product Features:	PLC Board (ISO 15118), Radio Frequency Identification (RFID)
Idle Mode Input Power (watts) AC- Input:	1010.27

No Vehicle Mode Input Power (watts) AC- Input:	33.78
No Vehicle Mode Power Factor AC-Input:	0.24
No Vehicle Mode Total Allowance (watts):	136.83
Partial On Mode Input Power (watts) AC-Input:	33.83
Partial On Mode Power Factor AC-Input:	0.24
Partial On Mode Total Allowance (watts):	136.83
Average Loading-Adjusted Efficiency (%) AC- Input:	0.95
Date Certified:	2023-08-14
Date Available On Market:	2023-07-31
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

Captured On: 07/04/2025