

ACIQ - Heat pump water heater : ACIQ-80G-HP-WH

Partner3628855ENRRY STAR Partner:1HVAC Energy, LLCBrand Name:ACIQModel Name:Heat pump water heaterModel Number:ACIQ-80G-HP-WHConnectd Capable:YesConnectd Using:Wi-Fi,CTA-2045-BCommunication Hardware Architecture:A-Built-inTime of Use Schedule:YesTax Credit Eligible:YesENRRY STAR Certified:YesTax Credit Eligible:YesType:Hybrid/Electric Heat PumpFuel:Hybrid/Electric Heat PumpFuel:240Input Voltage for HPWH (V):240Darw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (rf):7.4Inform Energy Factor (UEF):4.0Linger Compressor Cut Off Temperature for HPWH (rf):91Linform Energy Factor (UEF):4.0Refrigeran with GWP:9.1Refrigerant With GWP:4.0Refrigerant With GWP:9.1Linform Energy Factor (UEF):4.0Refrigerant With GWP:4.0Refrigerant With GWP:5.5Electric Input (kW):5.5Electric Input (kW):1.8Tank Height (inches):1.8Tank Height (inches):1.8Tank Height (inches):1.8Tank Height (inches):1.8Tank Height (inches):1.8Tank Height (inches):1.8 <th>Specifications</th> <th></th>	Specifications	
ENERGY STAR Partner:INVAC Energy, LLCBrand Name:ACIQModel Name:Heat pump water heaterModel Number:ACIQ-80G-HP-WHConnected Capable:YesConnects Using:Wi-FI, CTA-2045-DR Protocol:A - Built-inCommunication Hardware Architecture:A - Built-inTax Credit Eligible:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax Ampe:440Partern (Intended Usage):High-UsageIrget Hump Type:High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):91Refrigerant with GWP:10.6Refrigerant with GWP:4.0Inform Energy Factor (UEF):4.0Storage Volume (gallons):10.4Catoge (kWh/ry):124.0Storage Volume (gallons):5.5Electric Input (kW):124.0Storage Volume (gallons):14.0Tak Diamet (inches):13.8Tak Height (inches):14.7Tak Diamet (inches):14.7	- ENEDGY STAD Unique ID:	2626955
Brand Name:ACIQModel Name:Heat pump water heaterModel Number:ACIQ-80G-HP-WHConnected Capable:YesConnects Using:Wi-FLCTA-2045DR Protocol:CTA-2045-BCommunication Hardware Architecture:A - Built-inTime of Use Schedule:YesTax Credit Eligible:YesTax Credit Eligible:YesProtocol:YesFuer:Hybrid/Electric Heat PumpFuer:ElectricMax Amps:440Ingut Voltage for HPWH (V):240Partern (Intended Usage):High-UsageAFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for PuWH (F):7.4Vierger Compressor Cut Off Temperature for PuWH (F):9.1Refregrant with GWP:4.0Reforence (With):5.5Electric Logag (kWhyr):5.0Electric Logag (kWhyr):12.0Aradoma (Lagage):13.0Refregrant (Intende, Size):2.0Reforence (kWith):5.5Electric Logag (kWhyr):12.0Aradoma (Lagage):13.0Reforence (Lagage):13.0Reforence (Lagage (kWhyr):13.0Aradoma (Lagage):13.0Reforence (Lagage (kWhyr):13.0Reforence (Lagage (kWhyr):13.0Aradoma (Lagage):14.0Reforence (Lagage (kWhyr):21.0Reforence (Lagage (kWhyr):21.0Reforence (Lagage	·	
Model Name:Heat pump water heaterModel Number:ACIQ-80G-HP-WHConnected Capable:YesConnects Using:Wi-Fi,CTA-2045DR Protocol:CTA-2045-BCommunication Hardware Architecture:A - Built-inTime of Use Schedule:YesTax Credit Eligible:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:240Input Voltage for HPWH (V):91Yeattern (Intended Usage):High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):91.4Refrigerant with GWP:0.7.6Refrigerant with GWP:4.0Reforence (KWhyr):5.5Electric Linput (KW):5.5Electric Usage (KWhyr):140.0Reforence (KWhyr):140.0Rist Hour Rating (gallons):9.5Reforence (KWhyr):140.0Reforence (KWhyr):140.0Reforence (KWhyr):140.0Reforence (KWhyr):140.0Rist Haup Type:140.0Rist Haup Type:140.0Reforence (KWhyr):140.0Reforence (KWhyr):140.0Rist Haup Type:140.0Rist Haup Type:140.0Rist Haup Type:140.0Rist Haup Type:140.0Rist Haup Type:140.0Rist Haup Type:14		
Model Number:ACIQ-80G-HP-WHConnectel Capable:YesConnects Using:Wi-Fi,CTA-2045-BDR Protocol:A -Built-inCommunication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Pattern (Intended Usage):High-UsageFirst Hour Rating (galons):91Heat Pump Type:240.Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (F):7.4Refrigerant with GWP:A.134. (GWP:1430)Linform Energy Factor (UEF):4.0Recover Efficiency (%):5.5Electric Usage (kMhyr):124.0.0.Storage Volume (galons):7.4And7.4Electric Usage (kMhyr):21.8Arcade Ling Ling (Lingens):1.4And Lingens):1.4And Lingen		
Connected Capable:YesConnects Using:Wi-Fi,CTA-2045-BDR Protocol:CTA-2045-BCommunication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Pattern (Intended Usage):91Heat Pump Type:240 Volt Integrated HPWHElectrogetomycresor Cut Off Temperature for HPWH (*F):37.4Unform Energy Factor (UEF):4.0Recover Efficiency (%):4.5.5Electric Usage (kWh/yr):5.5Electric Usage (kWh/yr):21.8Atomatic Usage Science		
Connects Using:Wi-Fi,CTA-2045DR Protocol:CTA-2045-BCommunication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:VesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Arnps:24.0Input Voltage for HPWH (V):240Pare Partern (Intended Usage):High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH ("F):37.4Starger Artwith GWP:N.0Uniform Energy Factor (UEF):4.0Lectric Input (kW):5.5Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):7.4Ato-AndS.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):7.4Ato-And<		
DR Protocol:CTA-2045-BCommunication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:VesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH ("F):37.4Upper Compressor Cut Off Temperature for HPWH (F):107.6Inforn Energy Factor (UEF):4.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):74.0Tak Diameter (inches):21.8Tak Height (inches):21.8Tak Height (inches):202411-11	-	
Communication Hardware Architecture:A -Built-inTime of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:Hybrid/Electric Heat PumpType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):VesStarter (Intended Usage):High-UsageFirst Hour Rating (gallons):9Volt Integrated HPWH240 Volt Integrated HPWHInput Voltage for HPWH (V):9Starter (Intended Usage):9Heat Pump Type:240 Volt Integrated HPWHInput Voltage for HPWH100 Volt Integrated HPWHInput Voltage for HPWH100 Volt Integrated HPWHInput Compressor Cut Off Temperature for WHY (*F):107.6Inform Energy Factor (UEF):55Electric Input (KW):5.5Electric Input (kW):124.0Storage Volume (gallons):14.0Tak Diameter (Inches):12.8Tak Diameter (Inches):12.8Tak Height (Inches):12.4Storage Volume (see (Sing Constraint))10.7Storage Volume (see (Sing Constraint))12.8Tak Diameter (Inches):12.8Tak Diameter (Inches):12.4Storage Volume (see (Sing Constraint))12.8Tak Diameter (Inches):12.8Tak Diameter (Inches):12.8Tak Diameter (Inches):12.8Tak Diameter (Inches):12.4Tak Diameter (Inches):12.4Tak Diameter (Inches):12.4 </th <th>-</th> <th></th>	-	
Time of Use Schedule:YesTax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for PWH (*F):37.4Upper Compressor Cut Off Temperature for PWH (*F):107.6Conder Liefteieney (%):4.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):14.0Tak Diameter (inches):1.8Tak Diameter (inches):21.8Tak Height (inches):21.8Tak Height (inches):20.241111		
Tax Credit Eligible:YesENERGY STAR Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Pare Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHHower Compressor Cut Off Temperature for HPWH (*F):7.4Voltage for HPWE0.1Refrigeran with GWP:8.134a (GWP:1430)Refrigeran with GWP:5.5Electric Input (kW):5.5Electric Usage (kWh/yr):124.0Storage Volume (gallons):13.4At Laineter (inches):21.8Tak Diameter (inches):21.8At Height (inches):21.4Date Certified:21.4Storage Volume (selex):21.8Conterified:		
ENERGY STA Certified:YesType:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Storage Your Store (UEF):No16Refrigeran with GWP:R.134a (GWP:1430)Recovery Efficiency (%):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):1.4Tak Diameter (inches):1.8Ale Gallon (Singer Store):1.8Storage Volume (gallons):1.4Tak Height (inches):1.4Date Certified:20241111		
Type:Hybrid/Electric Heat PumpFuel:ElectricMax. Amps:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (°F):7.4Dyper Compressor Cut Off Temperature for HPWH (°F):8.134a (GWP:1430)Refrigerant with GWP:4.0Recovery Efficiency (%):5.5Electric Input (kW):5.4Storage Volume (gallons):7.4.0Tank Diameter (inches):21.8.2Date Certified:1.7.2Date Certified:20.24:11:1	-	
Fuel:ElectricMax. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Upper Compressor Cut Off Temperature for HPWH (*F):107.6Refrigerant with GWP:4.0Refrigerant with GWP:5.5Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):7.40Tank Diameter (inches):21.8Tank Height (inches):2024-11.11		
Max. Amps:24.0Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Dyper Compressor Cut Off Temperature for HPWH (*F):107.6Refrigerant with GWP:R-134a (GWP:1430)Recovery Efficiency (%):5.5Electric Input (kW):1240.0Storage Volume (gallons):1240.0Tank Diameter (inches):21.8Date Certified:21.8Cortified:21.8		
Input Voltage for HPWH (V):240Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (°F):37.4Upper Compressor Cut Off Temperature for HPWH (°F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):4.0Recovery Efficiency (%):5.5Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):7.4.0Tank Diameter (inches):21.8Date Certified:024-11-11		
Draw Pattern (Intended Usage):High-UsageFirst Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (*F):37.4Upper Compressor Cut Off Temperature for HPWH (*F):107.6Cut Different with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):4.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):74.0Tank Diameter (inches):21.8Date Certified:2024:11:11	•	
First Hour Rating (gallons):91Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (°F):37.4Upper Compressor Cut Off Temperature for HPWH (°F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):4.0Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):74.0Tank Diameter (inches):21.8Tank Height (inches):2024-11-11		
Heat Pump Type:240 Volt Integrated HPWHLower Compressor Cut Off Temperature for HPWH (°F):37.4Upper Compressor Cut Off Temperature for HPWH (°F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):4.0Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):74.0Tank Diameter (inches):21.8Tank Height (inches):2024-11-11		
Lower Compressor Cut Off Temperature for HPWH (*F):37.4Upper Compressor Cut Off Temperature for HPWH (*F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):4.0Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):74.0Tank Diameter (inches):21.8Tank Height (inches):2024-11-11		
HPWH (°F):Upper Compressor Cut Off Temperature for HPWH (°F):107.6Refrigerant with GWP:R-134a (GWP:1430)Uniform Energy Factor (UEF):4.0Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):74.0Tank Diameter (inches):21.8Tank Height (inches):41.7Date Certified:2024-11-11		
HPWH (°F):RRefrigerant with GWP:RRefrigerant with GWP:4.0Uniform Energy Factor (UEF):450.0Recovery Efficiency (%):5.5Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):74.0Tank Diameter (inches):21.8Tank Height (inches):41.7Date Certified:2024-11-11		37.4
Uniform Energy Factor (UEF):4.0Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):74.0Tank Diameter (inches):21.8Tank Height (inches):41.7Date Certified:2024-11-11		107.6
Recovery Efficiency (%):450.0Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):74.0Tank Diameter (inches):21.8Tank Height (inches):41.7Date Certified:2024-11-11	Refrigerant with GWP:	R-134a (GWP:1430)
Electric Input (kW):5.5Electric Usage (kWh/yr):1240.0Storage Volume (gallons):74.0Tank Diameter (inches):21.8Tank Height (inches):41.7Date Certified:2024-11-11	Uniform Energy Factor (UEF):	4.0
Electric Usage (kWh/yr):1240.0Storage Volume (gallons):74.0Tank Diameter (inches):21.8Tank Height (inches):41.7Date Certified:2024-11-11	Recovery Efficiency (%):	450.0
Storage Volume (gallons):74.0Tank Diameter (inches):21.8Tank Height (inches):41.7Date Certified:2024-11-11	Electric Input (kW):	5.5
Tank Diameter (inches):21.8Tank Height (inches):41.7Date Certified:2024-11-11	Electric Usage (kWh/yr):	1240.0
Tank Height (inches):41.7Date Certified:2024-11-11	Storage Volume (gallons):	74.0
Date Certified: 2024-11-11	Tank Diameter (inches):	21.8
	Tank Height (inches):	41.7
Markets: United States, Canada	Date Certified:	2024-11-11
	Markets:	United States, Canada

05/12/2025