



ENERGY STAR CERTIFIED

Uninterruptible Power Supplies

CyberPower - PR3000RTXL2UA : PR3000RTXL2UA

Specifications

ENERGY STAR Unique ID:	2323356
Brand Name:	CyberPower
Model Name:	PR3000RTXL2UA
Model Number:	PR3000RTXL2UA
Power Conversion Mechanism:	Static
Minimum Configuration Tested Model Number:	PR2200RTXL2UA
Active Output Power Rating Minimum Configuration (W):	2200
Apparent Output Power Rating Minimum Configuration (VA):	2200
Maximum Configuration Tested Model Number:	PR3000RTXL2UA
Active Output Power Rating Maximum Configuration (W):	3000
Topology (ac):	Line Interactive
Topology and Product Type Combined:	ac Line Interactive (VI)
Application:	Consumer
Rated Input Voltage (V rms):	100-120
Rated Input Frequency (Hz):	50-60
Rated Output Voltage (V):	100-120
Rated Output Frequency (Hz):	50-60
Rack Mountable:	Yes
Rack Mount Height (U):	2
Height (mm):	87
Width (mm):	433
Depth (mm):	630
Normal Mode(s) Input Dependency Characteristic (ac):	Voltage Independent
Modular UPS:	No
Number of Normal Modes:	Single-normal-mode
Default Normal Mode (ac):	Voltage Independent
Test Input Voltage (V rms):	120
Test Input Frequency (Hz):	60
Test Output Voltage (V):	120

Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	4.17
Efficiency at 25% Load Min Config Lowest Dependency (ac):	98.2
Efficiency at 50% Load Min Config Lowest Dependency (ac):	98.2
Efficiency at 75% Load Min Config Lowest Dependency (ac):	98.1
Efficiency at 100% Load Min Config Lowest Dependency (ac):	98.0
Weighted Efficiency Calc Min Config Lowest Dependency:	98.1
Total Input Power in W at 0% Load Max Config Lowest Dependency (ac):	5.34
Efficiency at 25% Load Max Config Lowest Dependency (ac):	98.8
Efficiency at 50% Load Max Config Lowest Dependency (ac):	98.8
Efficiency at 75% Load Max Config Lowest Dependency (ac):	98.5
Efficiency at 100% Load Max Config Lowest Dependency (ac):	98.2
Weighted Efficiency Calc Max Config Lowest Dependency:	98.5
Efficiency (%):	98.1
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	4
Energy Storage System Runtime at 50% Load (min.):	11
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	N/A
Network Connections Available:	Serial Port,Ethernet,USB Port
Communication Protocols:	HTTP,HTTPS,Other,SNMP (v1, 2 or 3)
Communication Protocol Other:	TCP/IP, UDP
Manufacturer Take Back Program:	Yes
Model Web Page URL:	N/A
Test Method Guidelines:	N/A
Date Available on Market:	2018-08-01
Date Certified:	2023-01-17
Markets:	United States, Taiwan, Japan, Canada

ENERGY STAR Certified:	Yes
------------------------	-----

Additional Model Information

PR2200RT2U JP,PR2200RT2U JP;; PR2200RT2U,PR2200RT2U;; PR2200RT2UC,PR2200RT2UC;;
PR2200RT2UCN,PR2200RT2UCN;; PR2200RTL2U JP,PR2200RTL2U JP;; PR2200RTL2U,PR2200RTL2U;;
PR2200RTL2UA JP,PR2200RTL2UA JP;; PR2200RTL2UA,PR2200RTL2UA;; PR2200RTL2UAC,PR2200RTL2UAC;;
PR2200RTL2UACN,PR2200RTL2UACN;; PR2200RTL2UC,PR2200RTL2UC;; PR2200RTL2UCN,PR2200RTL2UCN;;
PR3000RT2U JP,PR3000RT2U JP;; PR3000RT2U,PR3000RT2U;; PR3000RT2UC,PR3000RT2UC;;
PR3000RT2UCN,PR3000RT2UCN;; PR3000RTL2U JP,PR3000RTL2U JP;; PR3000RTL2U,PR3000RTL2U;;
PR3000RTL2UA JP,PR3000RTL2UA JP;; PR3000RTL2UAC,PR3000RTL2UAC;;
PR3000RTL2UACN,PR3000RTL2UACN;; PR3000RTL2UC,PR3000RTL2UC;; PR3000RTL2UCN,PR3000RTL2UCN;;
PRL3000RT2UC,PRL3000RT2UC;; PRL3000RT2UCN,PRL3000RT2UCN,

Captured On:
04/28/2025