

## Tripp Lite - AG-87C3 : ECO1500LCD

Specifications  ENERGY STAR Unique ID: 2329679  Brand Name: Tripp Lite  Model Name: AG-87C3  Model Number: EC01500LCD  Power Conversion Mechanism: Static  Minimum Configuration Tested Model Number: AG-87C3  Active Output Power Rating Minimum Configuration (W): P00  Apparent Output Power Rating Minimum Configuration (VA): 1440	
Brand Name: Tripp Lite  Model Name: AG-87C3  Model Number: EC01500LCD  Power Conversion Mechanism: Static  Minimum Configuration Tested Model Number: AG-87C3  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum 1440	
Model Name:  Model Number:  EC01500LCD  Power Conversion Mechanism:  Static  Minimum Configuration Tested Model Number:  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum 1440	
Model Number: EC01500LCD  Power Conversion Mechanism: Static  Minimum Configuration Tested Model AG-87C3  Number: Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum 1440	
Power Conversion Mechanism:  Minimum Configuration Tested Model Number:  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum 1440	
Minimum Configuration Tested Model Number:  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum  1440	
Number:  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum  1440	
Configuration (W):  Apparent Output Power Rating Minimum 1440	
Configuration (VA).	
Topology (ac): Passive Standby	
Topology and Product Type Combined: Alternating Current (ac) - Offline (	VFD)
Application: Commercial,Consumer	
Rated Input Voltage (V rms): 120-120	
Rated Input Frequency (Hz): 50-60	
Rated Output Voltage (V): 120-120	
Rated Output Frequency (Hz): 50-60	
Rack Mountable: No	
Rack Mount Height (U):	
Height (mm): 279	
<b>Width (mm):</b> 99	
<b>Depth (mm):</b> 410	
Total Number of Outlets: 5	
Number of Battery Backup and Surge Protected Outlets:  5	
Number of Surge Protected Only Outlets: 5	
Normal Mode(s) Input Dependency Characteristic (ac):  Voltage Independent	
Modular UPS:	
Number of Normal Modes: Single-normal-mode	
Default Normal Mode (ac): Voltage Independent	
Test Input Voltage (V rms):	
Test Input Frequency (Hz): 60	
Test Output Voltage (V):	

Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	0.06
Efficiency at 25% Load Min Config Lowest Dependency (ac):	97.7
Efficiency at 50% Load Min Config Lowest Dependency (ac):	98.6
Efficiency at 75% Load Min Config Lowest Dependency (ac):	98.8
Efficiency at 100% Load Min Config Lowest Dependency (ac):	98.7
Weighted Efficiency Calc Min Config Lowest Dependency:	98.7
Efficiency (%):	98.7
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
<b>Energy Storage System Configuration:</b>	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	3
Energy Storage System Runtime at 50% Load (min.):	11
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	N/A
Battery Recycling URL:	http://www.tripplite.com/en/support/recycling-program.cfm
Network Connections Available:	USB Port,Ethernet
Communication Protocols:	None
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	http://www.tripplite.com/en/support/recycling-program.cfm
Model Web Page URL:	https://www.tripplite.com/line-interactive-ups-with-usb-and-10-outlets-1500va-900w-avr-eco-series~ECO1500LCD
Test Method Guidelines:	N/A
Date Available on Market:	2018-05-01
Date Certified:	2018-11-14
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

**Captured On:** 05/22/2025