

## Tripp Lite - AG-0316 : EC0850LCD

| Specifications  ENERGY STAR Unique ID: 2332609  Brand Name: Tripp Lite  Model Name: AG-0316  Model Number: EC0850LCD  Power Conversion Mechanism: Static  Minimum Configuration Tested Model Number: AG-0316  Number: Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum 850 |  |
|---|--|
| Brand Name: Tripp Lite  Model Name: AG-0316  Model Number: EC0850LCD  Power Conversion Mechanism: Static  Minimum Configuration Tested Model Number: AG-0316  Active Output Power Rating Minimum Configuration (W): 425   |  |
| Model Name:  Model Number:  EC0850LCD  Power Conversion Mechanism:  Static  Minimum Configuration Tested Model Number:  Active Output Power Rating Minimum Configuration (W):  AG-0316  425   |  |
| Model Number: EC0850LCD  Power Conversion Mechanism: Static  Minimum Configuration Tested Model Number: AG-0316  Active Output Power Rating Minimum Configuration (W): 425  |  |
| Power Conversion Mechanism:  Minimum Configuration Tested Model Number:  Active Output Power Rating Minimum Configuration (W):  Static  AG-0316  425  |  |
| Minimum Configuration Tested Model Number:  Active Output Power Rating Minimum Configuration (W):  AG-0316  425   |  |
| Number: Active Output Power Rating Minimum Configuration (W): 425   |  |
| Configuration (W):  |  |
| Apparent Output Power Pating Minimum 050  |  |
| Configuration (VA):   |  |
| Topology (ac): Passive Standby  |  |
| <b>Topology and Product Type Combined:</b> Alternating Current (ac) - Offline (VFD)   |  |
| Application: Commercial,Consumer  |  |
| Rated Input Voltage (V rms): 120-120  |  |
| Rated Input Frequency (Hz): 50-60   |  |
| Rated Output Voltage (V): 120-120   |  |
| Rated Output Frequency (Hz): 50-60  |  |
| Rack Mountable: No  |  |
| Height (mm): 85   |  |
| <b>Width (mm):</b> 130  |  |
| <b>Depth (mm):</b> 320  |  |
| Total Number of Outlets: 12   |  |
| Number of Battery Backup and Surge Protected Outlets:  6  |  |
| Number of Surge Protected Only Outlets: 6   |  |
| Normal Mode(s) Input Dependency Characteristic (ac):  Voltage and Frequency Dependent   |  |
| Modular UPS:  |  |
| Number of Normal Modes: Single-normal-mode  |  |
| Default Normal Mode (ac):  Voltage and Frequency Dependent  |  |
| Test Input Voltage (V rms): 120   |  |
| Test Input Frequency (Hz): 60   |  |
| Test Output Voltage (V): 120  |  |
| Test Output Frequency (Hz): 60  |  |

| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): | 0.318   |
|--|---|
| Efficiency at 25% Load Min Config Lowest Dependency (ac):            | 97.7  |
| Efficiency at 50% Load Min Config Lowest Dependency (ac):            | 99.0  |
| Efficiency at 75% Load Min Config Lowest Dependency (ac):            | 99.3  |
| Efficiency at 100% Load Min Config Lowest Dependency (ac):           | 99.4  |
| Weighted Efficiency Calc Min Config Lowest Dependency:               | 99.0  |
| Efficiency (%):  | 99  |
| Modular UPS Module Tested Model Number:                              | N/A   |
| Energy Storage Mechanism:  | Battery   |
| Energy Storage System Technology:                                    | Valve Regulated Lead-acid Battery   |
| <b>Energy Storage System Configuration:</b>                          | Integral  |
| Energy Storage System Removable to Another Room:                     | No  |
| Energy Storage System Runtime at 100% Load (min.):                   | 2   |
| Energy Storage System Runtime at 50% Load (min.):                    | 9   |
| Energy Storage System Warranty (yrs):                                | 3   |
| Energy Storage System Information URL:                               | N/A   |
| Battery Recycling URL:   | http://www.tripplite.com/en/support/recycling-program.cfm   |
| <b>Network Connections Available:</b>                                | USB Port,Ethernet   |
| Communication Protocols:   | None  |
| Manufacturer Take Back Program:                                      | Yes   |
| Manufacturer Take Back Program URL:                                  | http://www.tripplite.com/en/support/recycling-program.cfm   |
| Model Web Page URL:  | https://www.tripplite.com/eco-series-120v-850va-425w-energy-saving-standby-ups-usb-lcd-display-12-outlets~ECO850LCD |
| Test Method Guidelines:  | N/A   |
| Date Available on Market:  | 2018-12-21  |
| Date Certified:  | 2019-01-03  |
| Markets:   | United States, Canada   |
| ENERGY STAR Certified:   | Yes   |
|  |   |

**Captured On:** 04/25/2025