



ENERGY STAR CERTIFIED

Uninterruptible Power Supplies

CyberPower - PR3000LCDSL : PR3000LCDSL

Specifications

ENERGY STAR Unique ID:	2333813
Brand Name:	CyberPower
Model Name:	PR3000LCDSL
Model Number:	PR3000LCDSL
Power Conversion Mechanism:	Static
Minimum Configuration Tested Model Number:	PR3000LCDSL
Active Output Power Rating Minimum Configuration (W):	2700
Apparent Output Power Rating Minimum Configuration (VA):	3000
Topology (ac):	Passive Standby
Topology and Product Type Combined:	Alternating Current (ac) - Offline (VFD)
Application:	Commercial,Consumer,Data Center
Rated Input Voltage (V rms):	120-120
Rated Input Frequency (Hz):	60-60
Rated Output Voltage (V):	120-120
Rated Output Frequency (Hz):	60-60
Rack Mountable:	No
Height (mm):	222
Width (mm):	170
Depth (mm):	233
Normal Mode(s) Input Dependency Characteristic (ac):	Voltage Independent
Modular UPS:	No
Number of Normal Modes:	Single-normal-mode
Default Normal Mode (ac):	Voltage Independent
Test Input Voltage (V rms):	120
Test Input Frequency (Hz):	60
Test Output Voltage (V):	120
Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	5.8
Efficiency at 25% Load Min Config Lowest Dependency (ac):	98.7

