



ENERGY STAR CERTIFIED

# Uninterruptible Power Supplies

## APC by Schneider Electric - APC Back UPS 650VA/360W Floor/Wall Mount 120V 7x NEMA 5-15R outlets USB Type A Port User Replaceable Battery : BVN650M1-CA

### Specifications

ENERGY STAR Unique ID:	2356214
Brand Name:	APC by Schneider Electric
Model Name:	APC Back UPS 650VA/360W Floor/Wall Mount 120V 7x NEMA 5-15R outlets USB Type A Port User Replaceable Battery
Model Number:	BVN650M1-CA
Power Conversion Mechanism:	Static
Minimum Configuration Tested Model Number:	BVN650M1
Active Output Power Rating Minimum Configuration (W):	360
Apparent Output Power Rating Minimum Configuration (VA):	650
Topology (ac):	Passive Standby
Topology and Product Type Combined:	Alternating Current (ac) - Offline (VFD)
Application:	Consumer
Rated Input Voltage (V rms):	120-120
Rated Input Frequency (Hz):	50-60
Rated Output Voltage (V):	120-120
Rated Output Frequency (Hz):	50-60
Rack Mountable:	No
Height (mm):	139
Width (mm):	105
Depth (mm):	274
Total Number of Outlets:	7
Number of Battery Backup and Surge Protected Outlets:	5
Number of Surge Protected Only Outlets:	2
Normal Mode(s) Input Dependency Characteristic (ac):	Voltage and Frequency Dependent
Modular UPS:	No
Number of Normal Modes:	Single-normal-mode
Default Normal Mode (ac):	Voltage and Frequency Dependent
Test Input Voltage (V rms):	120

<b>Test Input Frequency (Hz):</b>	60
<b>Test Output Voltage (V):</b>	120
<b>Test Output Frequency (Hz):</b>	60
<b>Efficiency at 25% Load Min Config Lowest Dependency (ac):</b>	98.0
<b>Efficiency at 50% Load Min Config Lowest Dependency (ac):</b>	98.9
<b>Efficiency at 75% Load Min Config Lowest Dependency (ac):</b>	99.1
<b>Efficiency at 100% Load Min Config Lowest Dependency (ac):</b>	99.1
<b>Weighted Efficiency Calc Min Config Lowest Dependency:</b>	98.8
<b>Efficiency (%):</b>	98.8
<b>Modular UPS Module Tested Model Number:</b>	N/A
<b>Energy Storage Mechanism:</b>	Battery
<b>Energy Storage System Technology:</b>	Valve Regulated Lead-acid Battery
<b>Energy Storage System Configuration:</b>	Integral
<b>Energy Storage System Removable to Another Room:</b>	No
<b>Energy Storage System Runtime at 100% Load (min.):</b>	2
<b>Energy Storage System Runtime at 50% Load (min.):</b>	10
<b>Energy Storage System Warranty (yrs):</b>	1
<b>Energy Storage System Information URL:</b>	<a href="https://www.se.com/us/en/product/APCRBCV211">https://www.se.com/us/en/product/APCRBCV211</a>
<b>Battery Recycling URL:</b>	<a href="https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp">https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp</a>
<b>Network Connections Available:</b>	None
<b>Communication Protocols:</b>	None
<b>Manufacturer Take Back Program:</b>	Yes
<b>Manufacturer Take Back Program URL:</b>	<a href="https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp">https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp</a>
<b>Model Web Page URL:</b>	<a href="https://www.se.com/ca/en/product/BVN650M1-CA">https://www.se.com/ca/en/product/BVN650M1-CA</a>
<b>Test Method Guidelines:</b>	N/A
<b>Date Available on Market:</b>	2020-03-10
<b>Date Certified:</b>	2020-02-26
<b>Markets:</b>	United States, Canada
<b>ENERGY STAR Certified:</b>	Yes

## Additional Model Information

APC Back UPS 650VA/360W Floor/Wall Mount 120V 7x NEMA 5-15R outlets USB Type A Port User Replaceable Battery Factory Serviced,BVN650M1-CAW,, Std Exch APC Back UPS 650VA/360W Floor/Wall Mount 120V 7x NEMA 5-15R outlets USB Type A Port User Replaceable Battery,BVN650M1-CAQ,

<b>UPC Codes</b>	731304413011
------------------	--------------

**Captured On:**  
04/25/2025