

## APC by Schneider Electric - Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Ports AVR LCD interface: BR1500MS2

ENERGY STAR Unique ID:  2365322  Brand Name:  APC by Schneider Electric  Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Ports AVR LCD interface		
Brand Name:         APC by Schneider Electric           Model Name:         Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Ports AVR LCD Interface           Model Number:         BR1500MS2           Power Conversion Mechanism:         Static           Minimum Configuration Tested Model Number:         BR1500MS           Active Output Power Rating Minimum Configuration (W):         900           Apparent Output Power Rating Minimum Configuration (VA):         1500           Topology (ac):         Line Interactive           Topology and Product Type Combined:         ac Line Interactive (VI)           Application:         Consumer           Rated Input Voltage (V rms):         120-120           Rated Input Frequency (Hz):         60-60           Rated Output Frequency (Hz):         60-60           Rated Output Frequency (Hz):         60-60           Rated Muntable:         No           Height (mm):         260           Wildth (mm):         100           Depth (mm):         368           Total Number of Outlets:         10           Number of Battery Backup and Surge Protected Outlets:         4           Normal Mode(s) Input Dependency Characteristic (ac):         No           Modular UPS:         No           Modular UPS:<	Specifications	
Model Name:         Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Ports AVR LCD interface           Model Number:         BR1500MS2           Power Conversion Mechanism:         Static           Minimum Configuration Tested Model Number:         BR1500MS           Active Output Power Rating Minimum Configuration (W):         900           Apparent Output Power Rating Minimum Configuration (VA):         1500           Topology (ac):         Line Interactive           Topology and Product Type Combined:         ac Line Interactive (VI)           Application:         Consumer           Rated Input Voltage (V rms):         120-120           Rated Input Frequency (Hz):         60-60           Rated Output Voltage (V):         120-120           Rated Output Voltage (V):         120-120           Rated Output Frequency (Hz):         60-60           Rack Mountable:         No           Height (mm):         260           Width (mm):         100           Depth (mm):         368           Total Number of Outlets:         10           Number of Battery Backup and Surge Protected Outly Outlets:         4           Normal Mode(s) Input Dependency Characteristic (ac):         No           Modular UPS:         No           No Induction	ENERGY STAR Unique ID:	2365322
Model Number: BR1500MS2  Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: BR1500MS Active Output Power Rating Minimum Pooriguration (W): Apparent Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Power (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Battery Backup and Surge Protected Outlets: 10 Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Brand Name:	APC by Schneider Electric
Power Conversion Mechanism:     Static       Minimum Configuration Tested Model Number:     BR1500MS       Active Output Power Rating Minimum Configuration (W):     900       Apparent Output Power Rating Minimum Configuration (VA):     1500       Topology (ac):     Line Interactive       Topology and Product Type Combined:     ac Line Interactive (VI)       Application:     Consumer       Rated Input Voltage (V rms):     120-120       Rated Input Frequency (Hz):     60-60       Rated Output Voltage (V):     120-120       Rated Output Frequency (Hz):     60-60       Rack Mountable:     No       Height (mm):     260       Width (mm):     100       Depth (mm):     368       Total Number of Outlets:     10       Number of Sattery Backup and Surge Protected Outlets:     4       Normal Mode(s) Input Dependency Characteristic (ac):     Voltage Independent       Modular UPS:     No       Number of Normal Modes:     Single-normal-mode       Default Normal Mode (ac):     Voltage Independent	Model Name:	Back UPS PRO BR 1500VA SineWave 10 Outlets 2 USB Charging Ports AVR LCD interface
Minimum Configuration Tested Model Number:  Active Output Power Rating Minimum Configuration (W):  Apparent Output Power Rating Minimum Configuration (VA):  Topology (ac):  Topology and Product Type Combined: Application: Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Ro-60 Rated Output Frequency (Hz): Ro-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Model Number:	BR1500MS2
Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No No Nomal Mode(s) Input Dependency Characteristic (ac): No No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Power Conversion Mechanism:	Static
Configuration (W):       1500         Apparent Output Power Rating Minimum Configuration (VA):       1500         Topology (ac):       Line Interactive         Topology and Product Type Combined:       ac Line Interactive (VI)         Application:       Consumer         Rated Input Voltage (V rms):       120-120         Rated Output Voltage (V):       120-120         Rated Output Frequency (Hz):       60-60         Rack Mountable:       No         Height (mm):       260         Width (mm):       100         Depth (mm):       368         Total Number of Outlets:       10         Number of Battery Backup and Surge Protected Outlets:       4         Normal Mode(s) Input Dependency Characteristic (ac):       Voltage Independent         Modular UPS:       No         Number of Normal Modes:       Single-normal-mode         Default Normal Mode (ac):       Voltage Independent		BR1500MS
Configuration (VA):Line InteractiveTopology (ac):Line Interactive (VI)Application:ConsumerRated Input Voltage (V rms):120-120Rated Input Frequency (Hz):60-60Rated Output Voltage (V):120-120Rated Output Frequency (Hz):60-60Rack Mountable:NoHeight (mm):260Width (mm):100Depth (mm):368Total Number of Outlets:10Number of Battery Backup and Surge Protected Outlets:6Number of Surge Protected Only Outlets:4Normal Mode(s) Input Dependency Characteristic (ac):NoModular UPS:NoNumber of Normal Modes:Single-normal-modeDefault Normal Mode (ac):Voltage Independent		900
Topology and Product Type Combined: Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Only Outlets: Voltage Independent Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent		1500
Application: Consumer Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Mumber of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Topology (ac):	Line Interactive
Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Topology and Product Type Combined:	ac Line Interactive (VI)
Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Application:	Consumer
Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Rated Input Voltage (V rms):	120-120
Rated Output Frequency (Hz): 60-60  Rack Mountable: No Height (mm): 260 Width (mm): 100 Depth (mm): 368 Total Number of Outlets: 10 Number of Battery Backup and Surge Protected Outlets: 4 Number of Surge Protected Only Outlets: 4 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent	Rated Input Frequency (Hz):	60-60
Rack Mountable:  Height (mm):  260  Width (mm):  100  Depth (mm):  368  Total Number of Outlets:  10  Number of Battery Backup and Surge Protected Outlets:  Number of Surge Protected Only Outlets:  4  Normal Mode(s) Input Dependency Characteristic (ac):  Modular UPS:  Number of Normal Modes:  Single-normal-mode  Default Normal Mode (ac):  Voltage Independent	Rated Output Voltage (V):	120-120
Height (mm): 260  Width (mm): 100  Depth (mm): 368  Total Number of Outlets: 10  Number of Battery Backup and Surge Protected Outlets: 4  Normal Mode(s) Input Dependency Characteristic (ac): No  Number of Normal Modes: Single-normal-mode  Default Normal Mode (ac): Voltage Independent	Rated Output Frequency (Hz):	60-60
Width (mm): 100  Depth (mm): 368  Total Number of Outlets: 10  Number of Battery Backup and Surge Protected Outlets: 4  Normal Mode(s) Input Dependency Characteristic (ac): Voltage Independent  Number of Normal Modes: Single-normal-mode  Default Normal Mode (ac): Voltage Independent	Rack Mountable:	No
Depth (mm):  Total Number of Outlets:  Number of Battery Backup and Surge Protected Outlets:  Number of Surge Protected Only Outlets:  Voltage Independent  Modular UPS:  No  Number of Normal Modes:  Single-normal-mode  Default Normal Mode (ac):  Voltage Independent	Height (mm):	260
Total Number of Outlets:  Number of Battery Backup and Surge Protected Outlets:  Number of Surge Protected Only Outlets:  Normal Mode(s) Input Dependency Characteristic (ac):  Modular UPS:  No Number of Normal Modes:  Single-normal-mode  Default Normal Mode (ac):  Voltage Independent  Voltage Independent	Width (mm):	100
Number of Battery Backup and Surge Protected Outlets:  Number of Surge Protected Only Outlets:  Normal Mode(s) Input Dependency Characteristic (ac):  Modular UPS:  No Number of Normal Modes:  Single-normal-mode  Default Normal Mode (ac):  Outlets:  4  Voltage Independent  Voltage Independent	Depth (mm):	368
Number of Surge Protected Only Outlets:  Normal Mode(s) Input Dependency Characteristic (ac):  Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac):  Voltage Independent  Voltage Independent	Total Number of Outlets:	10
Normal Mode(s) Input Dependency Characteristic (ac):  Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage Independent		6
Characteristic (ac):  Modular UPS: No Number of Normal Modes: Single-normal-mode  Voltage Independent	Number of Surge Protected Only Outlets:	4
Number of Normal Modes:  Default Normal Mode (ac):  Voltage Independent		Voltage Independent
Default Normal Mode (ac):  Voltage Independent	Modular UPS:	No
	Number of Normal Modes:	Single-normal-mode
Test Input Voltage (V rms): 120	Default Normal Mode (ac):	Voltage Independent
	Test Input Voltage (V rms):	120

Test Input Frequency (Hz):	60
Test Output Voltage (V):	120
Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	3.104
Efficiency at 25% Load Min Config Lowest Dependency (ac):	98.5
Efficiency at 50% Load Min Config Lowest Dependency (ac):	99.0
Efficiency at 75% Load Min Config Lowest Dependency (ac):	99.0
Efficiency at 100% Load Min Config Lowest Dependency (ac):	99.0
Weighted Efficiency Calc Min Config Lowest Dependency:	99.1
Efficiency (%):	99.1
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
<b>Energy Storage System Configuration:</b>	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	4
Energy Storage System Runtime at 50% Load (min.):	14
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	http://www.apc.com/shop/us/en/products/P-APCRBC163
Battery Recycling URL:	http://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Network Connections Available:	USB Port
Communication Protocols:	Other
Communication Protocol Other:	USB Power Summary
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	http://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp
Model Web Page URL:	http://www.apc.com/shop/us/en/products/P-BR1500MS2
Test Method Guidelines:	http://www.apc.com/us/en/who-we-are/sustainability/
Date Available on Market:	2020-08-30
Date Certified:	2020-08-30
Markets:	United States, Canada
<b>ENERGY STAR Certified:</b>	Yes

## **Additional Model Information**

Back UPS PRO 1500VA Sinewave 10 outlets 2 USB Charging ports AVR LCD Factory Serviced, BR1500MS2W,; Std Exch B ack UPS PRO 1500VA Sinewave 10 outlets 2 USB Charging ports AVR LCD, BR1500MS2Q,

**UPC Codes** 731304426103

**Captured On:** 04/25/2025