

Tripp Lite - AG-0309: AVR900U

| Specifications | |
|--|--------------------------|
| | |
| NERGY STAR Unique ID: | 2383395 |
| rand Name: | Tripp Lite |
| lodel Name: | AG-0309 |
| lodel Number: | AVR900U |
| ower Conversion Mechanism: | Static |
| linimum Configuration Tested Model umber: | AG-0309 |
| ctive Output Power Rating Minimum onfiguration (W): | 480 |
| pparent Output Power Rating Minimum onfiguration (VA): | 900 |
| opology (ac): | Line Interactive |
| opology and Product Type Combined: | ac Line Interactive (VI) |
| pplication: | Consumer,Commercial |
| ated Input Voltage (V rms): | 305-120 |
| ated Input Frequency (Hz): | 50-60 |
| ated Output Voltage (V): | 120-120 |
| ated Output Frequency (Hz): | 50-60 |
| ack Mountable: | No |
| eight (mm): | 105 |
| fidth (mm): | 190 |
| epth (mm): | 305 |
| otal Number of Outlets: | 6 |
| umber of Battery Backup and Surge rotected Outlets: | 6 |
| umber of Surge Protected Only Outlets: | 6 |
| ormal Mode(s) Input Dependency haracteristic (ac): | Voltage Independent |
| lodular UPS: | No |
| umber of Normal Modes: | Single-normal-mode |
| efault Normal Mode (ac): | Voltage Independent |
| est Input Voltage (V rms): | 120 |
| est Input Frequency (Hz): | 60 |
| est Output Voltage (V): | 120 |
| est Output Frequency (Hz): | 60 |

| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): | 2.25 |
|--|--|
| Efficiency at 25% Load Min Config Lowest Dependency (ac): | 9.8 |
| Efficiency at 50% Load Min Config Lowest Dependency (ac): | 9.9 |
| Efficiency at 75% Load Min Config Lowest Dependency (ac): | 9.9 |
| Efficiency at 100% Load Min Config Lowest Dependency (ac): | 9.9 |
| Weighted Efficiency Calc Min Config Lowest Dependency: | 99.3 |
| Efficiency (%): | 99.3 |
| Modular UPS Module Tested Model Number: | N/A |
| Energy Storage Mechanism: | Battery |
| Energy Storage System Technology: | Valve Regulated Lead-acid Battery |
| Energy Storage System Configuration: | Integral |
| Energy Storage System Removable to Another Room: | No |
| Energy Storage System Runtime at 100% Load (min.): | 10 |
| Energy Storage System Runtime at 50% Load (min.): | 3 |
| Energy Storage System Warranty (yrs): | 3 |
| Energy Storage System Information URL: | N/A |
| Battery Recycling URL: | http://www.tripplite.com/en/support/recycling-program.cfm |
| Network Connections Available: | Other,USB Port,Ethernet |
| Communication Protocols: | None |
| Manufacturer Take Back Program: | Yes |
| Manufacturer Take Back Program URL: | http://www.tripplite.com/en/support/recycling-program.cfm |
| Model Web Page URL: | https://www.tripplite.com/avr-series-120v-900va-480w-ultra-compact-line-interactive-ups-usb-port~AVR900U |
| Test Method Guidelines: | N/A |
| Date Available on Market: | 2019-10-08 |
| Date Certified: | 2021-07-28 |
| Markets: | United States, Canada |
| ENERGY STAR Certified: | Yes |
| | |

Captured On: 04/29/2025