



ENERGY STAR CERTIFIED

Uninterruptible Power Supplies

APC by Schneider Electric - Smart-UPS 2200VA SmartConnect TAA : SMT2200CUS

Specifications

| | |
|---|-----------------------------------|
| ENERGY STAR Unique ID: | 2698706 |
| Brand Name: | APC by Schneider Electric |
| Model Name: | Smart-UPS 2200VA SmartConnect TAA |
| Model Number: | SMT2200CUS |
| Power Conversion Mechanism: | Static |
| Minimum Configuration Tested Model Number: | SMT2200C |
| Active Output Power Rating Minimum Configuration (W): | 1920 |
| Apparent Output Power Rating Minimum Configuration (VA): | 2200 |
| Topology (ac): | Line Interactive |
| Topology and Product Type Combined: | ac Line Interactive (VI) |
| Application: | Commercial |
| Rated Input Voltage (V rms): | 110-125 |
| Rated Input Frequency (Hz): | 50-60 |
| Rated Output Voltage (V): | 110-125 |
| Rated Output Frequency (Hz): | 50-60 |
| Rack Mountable: | No |
| Height (mm): | 432 |
| Width (mm): | 196 |
| Depth (mm): | 544 |
| Total Number of Outlets: | 10 |
| Number of Battery Backup and Surge Protected Outlets: | 10 |
| Number of Surge Protected Only Outlets: | 0 |
| Normal Mode(s) Input Dependency Characteristic (ac): | Voltage Independent |
| Modular UPS: | No |
| Number of Normal Modes: | Single-normal-mode |
| Default Normal Mode (ac): | Voltage Independent |
| Test Input Voltage (V rms): | 120 |
| Test Input Frequency (Hz): | 60 |
| Test Output Voltage (V): | 120 |

| | |
|---|---|
| Test Output Frequency (Hz): | 60 |
| Total Input Power in W at 0% Load Min Config Lowest Dependency (ac): | 5.32 |
| Efficiency at 25% Load Min Config Lowest Dependency (ac): | 98.6 |
| Efficiency at 50% Load Min Config Lowest Dependency (ac): | 98.9 |
| Efficiency at 75% Load Min Config Lowest Dependency (ac): | 98.7 |
| Efficiency at 100% Load Min Config Lowest Dependency (ac): | 98.5 |
| Weighted Efficiency Calc Min Config Lowest Dependency: | 98.7 |
| Efficiency (%): | 98.7 |
| Modular UPS Module Tested Model Number: | N/A |
| Energy Storage Mechanism: | Battery |
| Energy Storage System Technology: | Valve Regulated Lead-acid Battery |
| Energy Storage System Configuration: | Integral |
| Energy Storage System Removable to Another Room: | No |
| Energy Storage System Runtime at 100% Load (min.): | 10 |
| Energy Storage System Runtime at 50% Load (min.): | 28 |
| Energy Storage System Warranty (yrs): | 2 |
| Energy Storage System Information URL: | https://www.apc.com/shop/us/en/products/P-RBC55 |
| Battery Recycling URL: | https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp |
| Network Connections Available: | Serial Port,Ethernet,USB Port |
| Communication Protocols: | Other,Modbus TCP,Modbus RTU |
| Communication Protocol Other: | USB Power Summary, Simple Signalling, SmartConnect |
| Manufacturer Take Back Program: | Yes |
| Manufacturer Take Back Program URL: | https://www.apc.com/us/en/who-we-are/sustainability/recycling-options.jsp |
| Model Web Page URL: | https://www.apc.com/us/en/product-category/88972-uninterruptible-power-supply-ups/ |
| Test Method Guidelines: | https://www.apc.com/us/en/who-we-are/sustainability/ |
| Date Available on Market: | 2024-01-05 |
| Date Certified: | 2023-10-31 |
| Markets: | United States |
| ENERGY STAR Certified: | Yes |

Captured On:
04/25/2025