

CyberPower - CP1000PFCRM1U: CP1000PFCRM1U

Brand Name: CyberPower Model Name: CP1000PFCRM1U Model Number: CP1000PFCRM1U Model Number: CP1000PFCRM1U Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Voltage (V): Rated Output Prequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Mountable: Yes Rack Mountable: Yes Rack Mount Height (U): 1 Height (mm): 44 Width (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Voltage and Frequency Independent Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode	Specifications	
Brand Name: CyberPower Model Name: CP1000PFCRM1U Model Number: CP1000PFCRM1U Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: CP1000PFCRM1U Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (W): Configuration (W): Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Configu	-	000007
Model Name: CP1000PFCRM1U Model Number: CP1000PFCRM1U Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: CP1000PFCRM1U Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (W): In Interactive Configuration (WA): Interactive Topology (ac): Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rated Output Frequency (Hz): 60-60 Rated Output Frequency (Hz): 120-120 Rack Mountable: Yes Rack Mount Height (U): 1 Height (mm): 44 Width (mm): 433 Depth (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Outlets: Number of Surge Protected Only Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60-60	•	
Model Number: CP1000FFCRM1U Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: CP1000FFCRM1U Active Output Power Rating Minimum Configuration (W): CP1000FCRM1U Active Output Power Rating Minimum Configuration (W): D00 Apparent Output Power Rating Minimum Configuration (VA): D00 Configuration (VA): Line Interactive Topology (ac): Line Interactive (VI) Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mount Height (U): 1 Height (mm): 44 Width (mm): 433 Depth (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: Number of Battery Backup and Surge Protected Outlets: No Number of Surge Protected Only Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): No Noundular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Test Input Frequency (Hz): 60 Test Input Frequency (Hz): 60		
Power Conversion Mechanism: Static Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Voltage (V): 120-120 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: Yes Rack Mount Height (U): 1 Height (mm): 44 Width (mm): 433 Depth (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: 1 Number of Battery Backup and Surge Protected Outlets: No No No No No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60 Output Frequency (Hz): 120 Test Input Frequency (Hz): 60		
Minimum Configuration Tested Model Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): Rated Input Voltage (V rms): Rated Input Frequency (Hz): Rated Output Prequency (Hz): Rated Output Prequency (Hz): Rated Output Frequency (Hz): Rated Output Frequency (Hz): Rated Muntable: Rack Mountable: Rack Mount Height (U): Height (rmm): 44 Width (rmm): 389 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Voltage and Frequency Independent Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 600		CP1000PFCRM1U
Number: Active Output Power Rating Minimum Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: Application: Rated Input Voltage (V rms): Rated Input Voltage (V rms): Rated Input Voltage (V): Rated Input Frequency (Hz): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Rated Output Frequency (Hz): Rated Mountable: Rack Mountable: Rack Mountable: Rack Mount Height (U): Height (mm): 44 Width (mm): 389 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 600	Power Conversion Mechanism:	Static
Configuration (W): Apparent Output Power Rating Minimum Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): Rated Input Voltage (V rms): Rated Input Frequency (Hz): Act Output Voltage (V): Rated Output Voltage (V): Rated Output Voltage (V): Rated Output Frequency (Hz): Act Mountable: Yes Rack Mountable: Yes Rack Mount Height (U): Height (mm): Ad3 Depth (mm): A33 Depth (mm): B389 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Voltage and Frequency Independent Characteristic (ac): Modular UPS: No No Number of Normal Modes: Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): Botal Capter Surge Protected (V rms): 120 Test Input Frequency (Hz): Botal Capter Surge Protected (V rms): 120 Test Input Frequency (Hz): Botal Capter Surge Protected (V rms): 120 Test Input Frequency (Hz): Botal Capter Surge Protected (Va): Bota	Minimum Configuration Tested Model Number:	CP1000PFCRM1U
Configuration (VA): Topology (ac): Line Interactive Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: Yes Rack Mountable: Yes Rack Mount Height (U): 1 Height (mm): 44 Width (mm): 433 Depth (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 6 60	Active Output Power Rating Minimum Configuration (W):	600
Topology and Product Type Combined: ac Line Interactive (VI) Application: Data Center, Consumer, Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: Yes Rack Mount Height (U): 1 Height (mm): 44 Width (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outle ts: Number of Surge Protected Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60	Apparent Output Power Rating Minimum Configuration (VA):	1000
Application: Data Center,Consumer,Commercial Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: Yes Rack Mount Height (U): 1 Height (mm): 44 Width (mm): 433 Depth (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): Voltage and Frequency Independent Characteristic (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60	Topology (ac):	Line Interactive
Rated Input Voltage (V rms): 120-120 Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: Yes Rack Mount Height (U): 1 Height (mm): 44 Width (mm): 433 Depth (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Only Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): Voltage and Frequency Independent Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60	Topology and Product Type Combined:	ac Line Interactive (VI)
Rated Input Frequency (Hz): 60-60 Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: Yes Rack Mount Height (U): 1 Height (mm): 44 Width (mm): 433 Depth (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Only Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): Voltage and Frequency Independent Characteristic (ac): Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60	Application:	Data Center,Consumer,Commercial
Rated Output Voltage (V): 120-120 Rated Output Frequency (Hz): 60-60 Rack Mountable: Yes Rack Mount Height (U): 1 Height (mm): 44 Width (mm): 433 Depth (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60	Rated Input Voltage (V rms):	120-120
Rated Output Frequency (Hz): 60-60 Rack Mountable: Yes Rack Mount Height (U): 1 Height (mm): 44 Width (mm): 433 Depth (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60	Rated Input Frequency (Hz):	60-60
Rack Mount Height (U): Height (mm): 44 Width (mm): 433 Depth (mm): 389 Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage and Frequency Independent Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 6	Rated Output Voltage (V):	120-120
Rack Mount Height (U): Height (mm): 44 Width (mm): 433 Depth (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Voltage and Frequency Independent Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz):	Rated Output Frequency (Hz):	60-60
Height (mm): Width (mm): 433 Depth (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Single-normal-mode Default Normal Mode (ac): Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60	Rack Mountable:	Yes
Width (mm): Depth (mm): 389 Total Number of Outlets: 6 Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Voltage and Frequency Independent 120 Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60	Rack Mount Height (U):	1
Depth (mm): Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Default Normal Mode (ac): Test Input Voltage (V rms): Test Input Frequency (Hz): 389 4 A A A A A A A A A A A A	Height (mm):	44
Total Number of Outlets: Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Test Input Voltage (V rms): 120 Test Input Frequency (Hz):	Width (mm):	433
Number of Battery Backup and Surge Protected Outlets: Number of Surge Protected Only Outlets: Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Voltage and Frequency Independent 120 Test Input Frequency (Hz): 60	Depth (mm):	389
Protected Outlets: 2 Normal Mode(s) Input Dependency Characteristic (ac): Voltage and Frequency Independent Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60	Total Number of Outlets:	6
Normal Mode(s) Input Dependency Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60	Number of Battery Backup and Surge Protected Outlets:	4
Characteristic (ac): Modular UPS: No Number of Normal Modes: Single-normal-mode Default Normal Mode (ac): Voltage and Frequency Independent Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60	Number of Surge Protected Only Outlets:	2
Number of Normal Modes: Default Normal Mode (ac): Voltage and Frequency Independent 120 Test Input Frequency (Hz): 60	Normal Mode(s) Input Dependency Characteristic (ac):	Voltage and Frequency Independent
Default Normal Mode (ac): Voltage and Frequency Independent 120 Test Input Frequency (Hz): 60	Modular UPS:	No
Test Input Voltage (V rms): 120 Test Input Frequency (Hz): 60	Number of Normal Modes:	Single-normal-mode
Test Input Frequency (Hz): 60	Default Normal Mode (ac):	Voltage and Frequency Independent
	Test Input Voltage (V rms):	120
Test Output Voltage (V): 120	Test Input Frequency (Hz):	60
	Test Output Voltage (V):	120

Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	3.31
Efficiency at 25% Load Min Config Lowest Dependency (ac):	97.3
Efficiency at 50% Load Min Config Lowest Dependency (ac):	98.5
Efficiency at 75% Load Min Config Lowest Dependency (ac):	98.6
Efficiency at 100% Load Min Config Lowest Dependency (ac):	98.6
Weighted Efficiency Calc Min Config Lowest Dependency:	98.6
Efficiency (%):	98.6
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	2
Energy Storage System Runtime at 50% Load (min.):	11
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	https://www.cyberpowersystems.com/
Battery Recycling URL:	https://www.cyberpowersystems.com/faqs/what-should-i-do-with-spent-batteries/
Network Connections Available:	Serial Port,Ethernet
Communication Protocols:	HTTP,HTTPS,SNMP (v1, 2 or 3)
Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	https://www.cyberpowersystems.com/faqs/how-do-i-dispose-of-my-ups/
Model Web Page URL:	http://www.cyberpowersystems.com/
Test Method Guidelines:	https://www.cyberpowersystems.com/
Date Available on Market:	2024-05-15
Date Certified:	2024-01-11
Markets:	United States
ENERGY STAR Certified:	Yes

Additional Model Information

CP1200PFCRM1U,CP1200PFCRM1U,; CP1500PFCRM1U,CP1500PFCRM1U,

UPC Codes 649532936854