

CyberPower - GX950UC : GX950UC

Specifications	
ENERGY STAR Unique ID:	3891826
Brand Name:	CyberPower
Model Name:	GX950UC
Model Number:	GX950UC
Power Conversion Mechanism:	Static
Minimum Configuration Tested Model Number:	GX900UC
Active Output Power Rating Minimum Configuration (W):	480
Apparent Output Power Rating Minimum Configuration (VA):	900
Maximum Configuration Tested Model Number:	GX950UC
Active Output Power Rating Maximum Configuration (W):	510
Topology (ac):	Passive Standby
Topology and Product Type Combined:	Alternating Current (ac) - Offline (VFD)
Application:	Data Center,Consumer,Commercial
Rated Input Voltage (V rms):	120-120
Rated Input Frequency (Hz):	50-60
Rated Output Voltage (V):	120-120
Rated Output Frequency (Hz):	50-59
Rack Mountable:	No
Height (mm):	138
Width (mm):	324
Depth (mm):	70
Total Number of Outlets:	7
Number of Battery Backup and Surge Protected Outlets:	5
Number of Surge Protected Only Outlets:	2
Normal Mode(s) Input Dependency Characteristic (ac):	Voltage and Frequency Dependent
Modular UPS:	No
Number of Normal Modes:	Single-normal-mode
Default Normal Mode (ac):	Voltage and Frequency Dependent
Test Input Voltage (V rms):	120

Test Input Frequency (Hz):	60
Test Output Voltage (V):	120
Test Output Frequency (Hz):	60
Total Input Power in W at 0% Load Min Config Lowest Dependency (ac):	2.17
Efficiency at 25% Load Min Config Lowest Dependency (ac):	99.0
Efficiency at 50% Load Min Config Lowest Dependency (ac):	99.6
Efficiency at 75% Load Min Config Lowest Dependency (ac):	99.6
Efficiency at 100% Load Min Config Lowest Dependency (ac):	99.5
Weighted Efficiency Calc Min Config Lowest Dependency:	99.4
Total Input Power in W at 0% Load Max Config Lowest Dependency (ac):	2.32
Efficiency at 25% Load Max Config Lowest Dependency (ac):	98.6
Efficiency at 50% Load Max Config Lowest Dependency (ac):	99.4
Efficiency at 75% Load Max Config Lowest Dependency (ac):	99.3
Efficiency at 100% Load Max Config Lowest Dependency (ac):	99.4
Weighted Efficiency Calc Max Config Lowest Dependency:	99.2
Maximum Configuration Input Power Factor Lowest-Input Dependency:	0.99
Maximum Configuration Input Power Factor Highest-Input Dependency:	0.99
Efficiency (%):	99.4
Modular UPS Module Tested Model Number:	N/A
Energy Storage Mechanism:	Battery
Energy Storage System Technology:	Valve Regulated Lead-acid Battery
Energy Storage System Configuration:	Integral
Energy Storage System Removable to Another Room:	No
Energy Storage System Runtime at 100% Load (min.):	1
Energy Storage System Runtime at 50% Load (min.):	7
Energy Storage System Warranty (yrs):	3
Energy Storage System Information URL:	https://www.cyberpowersystems.com/
Battery Recycling URL:	What should I do with spent batteries? CyberPower (cyberpowersystems.com)
Network Connections Available:	None
Communication Protocols:	None
1	

Manufacturer Take Back Program:	Yes
Manufacturer Take Back Program URL:	https://www.cyberpowersystems.com/faqs/how-do-i-dispose-of-my- ups/
Model Web Page URL:	http://www.cyberpowersystems.com/
Test Method Guidelines:	https://www.cyberpowersystems.com/
Date Available on Market:	2025-04-01
Date Certified:	2024-12-23
Markets:	United States, Canada
ENERGY STAR Certified:	Yes

Captured On: 05/23/2025